

CHEMOTEX Děčín a. s.
Děčín XXXII – Boletice nad Labem 63
407 11 Děčín
Czech Republic

Phone: +420-412-547 461
Fax: +420-412-547 739
E-mail: chemotex@chemotex.cz
www.chemotex.cz

FLORE WC GEL EUKALYPTUS

TECHNICAL SHEET TL 687/2013

Date of issue: 17.10.2013

Date of revision: 27.6.2017

Chemical characteristics of the product

FLORE WC GEL is an acidic sanitizer based on organic and inorganic acids and special surfactants

Use

FLORE WC GEL Is mainly used for municipal hygiene.

- **EASILY REMOVES RUST**
- **REMOVES LIMESCALE**
- **HIGH CLEANING EFFECTIVITY**
- **LIMITS FURTHER DEPOSITION**
- **CLEANS BATHS, WASHBASINS AND WC**
- **LEAVES FRESH FRAGRANCE**

Product features

FLORE WC GEL is a clear viscous liquid with a refreshing scent.

FLORE WC GEL must comply with these quality signs:

Quality sign	Value	Methodology of determination
Sry matter in %	min. 13	PN-ZM 687/2015
pH of the sample	1 to 3	PN-ZM 687/2015
Consistencdy by 23 °C/F4 in s	min. 80	DIN 53211
Appearance	Clear, medium viscous liquid	visually

Product processing

Lightly spray the product under the edge of the toilet bowl. Let briefly work, then rinse with water. In case of severe contamination, let the product work longer.

The product is also suitable for washing floors and tiles. Wash the bath by adding 2 tablespoons of the product to 5 liters of lukewarm water. In the case of greater contamination, the concentration may be increased or the solution left on for several minutes.

Packaging, storage

FLORE WC GEL is delivered in PE bottles with a safety cap, in a 25 and 50 liters PE cans or in other pre-agreed packages.

Store in closed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 ° C. Short-term exposure to lower temperatures, such as during transport, does not affect the application characteristics of the product.

Transport

FLORE WC GEL is transported by covered means of transport. Not subject to ADR / RID regulations.

Shelf life

When the product is transported and stored in accordance with the above conditions, its shelf life is 24 months from the date of production._

Note

Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical sheet can only give a legal advice without obligation, the processing of the product must be adapted to the specific conditions.