

CHEMOTEX Děčín a. s.

Děčín XXXII – Boletice nad Labem 63

407 11 Děčín

Czech Republic

Phone: +420-412-709 222

Fax: +420-412-547 739

E-mail: chemotex@chemotex.cz

www.chemotex.cz

AVISIL – FABRIC SOFTENER (FABRIC SOFTENER)

TECHNICAL SHEET TL 796/2017

Date of issue: 16.6.2017

Date of revision: -

Product characteristics

AVISIL – FABRIC SOFTENER an aqueous solution of a di-alkyl (C₁₀-C₂₀) ester of the quaternary triethanolamine salt of dimethyl sulfate

With the addition of perfume and preservatives.

It is produced in these market types:

AVISIL – MAGIC SOFTNESS

AVISIL – SLEEP FULL OF SCENT

AVISIL – BLACK PEARL

AVISIL – WILD ORCHID

AVISIL – ALPINE AIR

Use

AVISIL – FABRIC SOFTENER is a softener for softening and antistatic treatment of textiles.

Protects fiber, prevents the origin of electrostatic charge and makes ironing easier. Helps to prevent fading of colors, so the laundry will look like new longer.

Product features

AVISIL – FABRIC SOFTENER is a medium-viscous liquid of white color with a fresh fragrance.

Biodegradable.

AVISIL – FABRIC SOFTENER must comply with these quality signs:

Quality sign	Value	Methodology of determination
Sry matter in %	min. 8	PN-ZM 796/2017
pH 3% of solution	3 to 5	PN-ZM 796/2017
Appearance	White homogeneous liquid	visually

Product processing

AVISIL – FABRIC SOFTENER is added to the last rinsing bath.

Dosage - 20 to 30 ml for 4 to 5 kg of laundry.

Packaging, storage

AVISIL - FABRIC SOFTENER is delivered in 1 or 2 liter PE bottles or in other pre-agreed packages. Store in closed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 ° C. Protect against frost!

Transport

AVISIL – FABRIC SOFTENER is transported by covered means of transport in accordance with ADR / RID regulations.

Shelf life

If the product is transported and stored in accordance with the above conditions its shelf life is 24 months from the date of release from the stock.

Note

Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical sheet can only give a legal advice without obligation, the processing of the product must be adapted to the specific conditions.