CHEMOTEX Děčín a. s.

Děčín XXXII – Boletice nad Labem 63 407 11 Děčín

Czech Republic

Phone: +420-412-709 222 Fax: +420-412-547 739

E-mail: chemotex@chemotex.cz

www.chemotex.cz

FLORE ULTRA

(CHERRY, POMEGRANATE, LIME, GREEN APPLE, ALOE VERA)

TECHNICAL SHEET TL 715/2015

Date of issue: 9.3.2015 Date of revision: 15.6.2017

Chemical characteristics of the product

A water solution of a mixture of surfactants, pleasantly perfumed.

<u>Use</u>

FLORE ULTRA is used as a very effective hand dishwashing product.

Product features

FLORE ULTRA is a clear, medium viscous liquid with a fresh fragrance. It is produced in these types.

FLORE ULTRA must comply with these quality signs:

Quality sign	Value	Methodology of determination
Dry matter in %	min. 12	PN-ZM 715/2015
pH 3% of water solution	6 to 8	PN-ZM 715/2015
Consistency by 23 °C/F4 in s	min. 100	DIN 56211

Product processing

An effective dishwashing solution is prepared by diluting 1 to 2 tablespoons (8 to 16 ml) of the composition into 5 liters of water. The product is also effective in cold water. After work, we recommend that you rinse your dishes under running water and treat your skin with a reparative cream. The product contains dermatologically favorable surfactants.

Packaging, storage

FLORE ULTRA is supplied in PET bottles of 500 ml and 1 liter capacity, in PE canisters of 5 and 10 liters capacity or in other pre-agreed packages. Store in closed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 ° C.

The product must be protected from frost!

Transport

FLORE ULTRA is transported by covered means of transport. Not subject to ADR / RID regulations.

Shelf life

When the product is transported and stored in accordance with the above conditions, is its shelf life 24 months from the date of production._

Note Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical sheet can only give a legal advice without obligation, the processing of the product must be adapted to the specific conditions.
TI 715/2015 FLODE III TDA