

**CHEMOTEX Děčín a.s.**

Tovární 63

407 11 Děčín XXXII - Boletice n. L.

Czech Republic

**Tel: +420-412-709 222****Fax: +420-412-547 200****E-mail: chemotex@chemotex.cz****www.chemotex.cz****Ebol EM-SCH****TECHNICAL DATA SHEET****TL 297/2002**

Date of issue: 17.06.2002

Revision date: 27.11.2011

**Product characteristics****EBOL EM-SCH** is a surface active agent of a non-ionic background.**Use****EBOL EM-SCH** is used as non-ionic detergent into washing and cleaning preparations. It is utilizable as emulsifier, dispersing agent and wetting agent as well.**Product features****EBOL EM-SCH** je při normální teplotě bezbarvá až nažloutlá středně viskózní kapalina se sklonem k sedimentaci.**Mísitelnost EBOLu EM-SCH (10 % při 23 °C):**

Destilovaná voda	Pitná voda (2,7 mmol Ca <sup>2+</sup> /l)	Hydroxid sodný (5%)	Kyselina chlorovodíková	Chlorid sodný (5%)	Solventní nafta	Ethanol	Aromatické uhlovodíky
+	+	o	+	+	*	+	+

+ = čirý roztok

\* = těžko rozpustný (nerozpustný sediment)

- = nerozpustný

o = neprůhledná emulze

**Product manufacturing****EBOL EM-SCH** is applicable in 1,5 to 10 % concentrations into that products targeted the washing dishes, universal washing preparations as well as some types of formulations of washing pastes. By the application of this product you can take advantage of its high degreasing ability on the one hand and lowered foaming ability on the other. Furthermore, **EBOL EM-SCH** might also be used as emulsifier, dispersing agent as well as wetting agent.**Packing and storage****EBOL EM-SCH** is delivered in polyethylene cans (50 litres) or in other packages that have been discussed in advance. Product is stored in closed containers in temperatures within +5 up to +25 °C. Product must be protected from direct weather influences. If the product is exposed to temperatures below 0 °C it does not have any negative effects on the application properties of the product.**Transport****EBOL EM-SCH** is transported in covered vehicles and is not subject to the ADR/RID regulations.**Warranty**

If the product is transported and stored according to the above mentioned conditions, the warranty is 6 months

from the date of stock-out.

**Note**

Data about the product characteristics and its manufacturing were acquired by laboratory measurements and application tests. This technical sheet can only give a legal advice without any obligation. The manufacturing of the product must be adjusted to the specific conditions.

